



Fimco Standard Spot Sprayer - 15 gal

RFLG13P



Details

Fimco 15 and 25 gallon sprayers with corrosion resistant polyethylene tank feature lower tank profile for improved stability. Full drain out capability with molded-in drain port, cap and tether. Large pick-up sump. 5" fill lid with tether. 15' handgun hose. 18" lever handgun with adjustable pattern tip. 12 volt demand diaphragm 2.1 GPM; 60 psi. High-Flo pump. Maximum horizontal throw 30'. Maximum vertical throw 15'. Made in USA.

- 15 gallon corrosion-resistant polyethylene tank
- 5" fill lid with tether
- Full drain-out capability w/ molded-in drain port, cap & tether
- 15' handgun hose
- 18" lever handgun with adjustable pattern tip
- Large pick-up sump
- 12V demand diaphragm 2.1 GMP High-Flo pump
- Max horizontal throw: 30 ft.
- Max vertical throw: 15 ft.
- 8 ft. lead wire with Quick Connect
- Full length sump
- Both gallon and liter fluid volume indicator
- Molded wand clips

Specifications

Manufacturer	Fimco
Capacity	15 gal
Flow Rate	2.1 gpm
Manufacturer's Warranty	1 year
Material	Corrosion-Resistant Polyethylene
Maximum Pressure	60 psi
Spray Vertical Height	15 ft

Krima Trading AB

Stene 710 Kumla, 692 93

+46 19 57 35 20

<https://krima.rrproducts.com/>