



Alloy Hollow Side-Eject Tine - .750MT x 6.500L x .470OD R108-9162



Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine.

Replaces

| | |
|--------------|-----------|
| R&R Products | R106-8947 |
| Toro | 108-9162 |

Specifications

| | |
|----------------------------------|-------------------------|
| Manufacturer | R&R Products |
| A - Tine Type | Alloy Hollow Side-Eject |
| B - Tine Mounting Dia. | .750 in (19mm) |
| C - Tine Length | 6.5 in (165mm) |
| D - Tine Tip Outside (Hole) Dia. | .470 in (11.9mm) |
| E - Tine Tip Inside (Core) Dia. | .300 in (7.6mm) |
| F - Tine Wall Thickness | .058 in (1.5mm) |

Fits Models

Toro ProCore 1298
Toro ProCore 440
Toro ProCore 648
Toro ProCore 660
Toro ProCore 864
Toro ProCore 880
Toro ProCore 648s

Krima Trading AB

Stene 710 Kumla, 692 93
+46 19 57 35 20

<https://krima.rrproducts.com/>