

Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .5250D R201511





Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

R&R Products R108-9172 Toro 108-9172

Specifications

Manufacturer

A - Tine Type Alloy Hollow Side-Eject with Carbide Tip B - Tine Mounting .750 in (19mm) Dia. C - Tine Length 4.75 in (121mm) Carbide Tip Carbide Tip D - Tine Tip Outside .525 in (13.3mm) (Hole) Dia. E - Tine Tip Inside .350 in (8.9 mm) (Core) Dia. F - Tine Wall .072 in (1.8mm) **Thickness** Savings Volume Buy

R&R Products

Krima Trading AB Stene 710 Kumla, 692 93 +46 19 57 35 20

https://krima.rrproducts.com/



Alloy Hollow Side-Eject Tine with Carbide Tip - .750MT x 4.750L x .5250D R201511



Fits Models

Jacobsen GA-24

Ryan Greensaire II

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s