

Alloy Hollow Tine with Carbide Tip - .750MT x 4.750L x .630OD







Details

Carbide-Tipped Alloy Hollow Tine construction uses the same special high carbon alloy steel tubing and hardened to RC45-48 as the alloy hollow tines, with the addition of a carbide tip for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines. You can expect these tines to last 6-8 times longer than the R&R Standard Hollow Tines. Carbide-tipped tines are not recommended in rocky soil conditions, as carbide, which is extremely wear resistant, can break when encountering hard impacts in rocks.

Replaces

R&R Products R108-9143 Toro 108-9143

Specifications

Manufacturer **R&R Products** A - Tine Type Alloy Hollow with Carbide Tip B - Tine Mounting .750 in (19mm) Dia. C - Tine Length 4.75 in (121mm) Carbide Tip Carbide Tip D - Tine Tip Outside .630 in (16mm) (Hole) Dia. E - Tine Tip Inside .480 in (1.22mm) (Core) Dia. F - Tine Wall .072 in (1.8mm)

Fits Models

Jacobsen GA-24

Thickness

Krima Trading AB Stene 710 Kumla, 692 93 +46 19 57 35 20

https://krima.rrproducts.com/



Alloy Hollow Tine with Carbide Tip - .750MT x 4.750L x .630OD R201512



Ryan Greensaire II

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s