

Alloy Hollow Tine - .750MT x 5.500L x .670OD





R201589

Details

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

Replaces

R&R Products

R201589S

Specifications

Manufacturer	R&R Products
A - Tine Type	Alloy Hollow
B - Tine Mounting	.750 in (19mm)
Dia.	
C - Tine Length	5.500 in (140mm)
D - Tine Tip Outside	.670 in (17mm)
(Hole) Dia.	
E - Tine Tip Inside	.500 in (12.7mm)
(Core) Dia.	
F - Tine Wall	.072 in (1.8mm)
Thickness	

Fits Models

John Deere Aercore 1000 John Deere Aercore 1500 John Deere Aercore 2000 John Deere Aercore 800 Ryan GA30

Krima Trading AB Stene 710 Kumla, 692 93

Stene 710 Kumla, 692 93 +46 19 57 35 20 https://krima.rrproducts.com/